

MAX-P Platform Price Computing Scale

- ◆ Large single load cell design
- ◆ Indicator with swivel wheels (up, down 45 ° and level 360 °), easy adjust on viewing angle
- ◆ Large 6 digits LCD (108 mm x 27 mm / 4.25" x 1.06") with backlight
- ◆ Built- in long life rechargeable battery, each charge for approximately 100 hours
- ◆ Rugged aluminum die-casting injection construction
- ◆ Sub-total recall and change calculating function
- ◆ Addition, subtraction and multiplication of non-weighed items
- ◆ Auto calibration
- ◆ With RS-232 interface
- ◆ **Optional :**
Stainless steel pole 400 mm or 665 mm



ITEM NO.	MAX-P30	MAX-P60	MAX-P150	MAX-P300
CAPACITY	30 kg	60 kg	150 kg	300 kg
SENSITIVITY	10 g	20 g	50 g	100 g
PLATFORM SIZE	430x330mm	430x330mm 525x425mm	430x330mm 525x425mm	525x425mm
POWER SOURCE	6V rechargeable battery			
PACKING	1 set / CTN, N.W.: 10.44 kg, G.W.: 12.30 kg, Cuft: 2.4'			
	1 set / CTN, N.W.: 16.72 kg, G.W.: 18.66 kg, Cuft: 2.9'			

MAX - C Platform Counting Scale MAX - CH

- ◆ Large single load cell design
- ◆ Indicator with swivel wheels (up, down 45 ° and level 360 °), easy adjust on viewing angle
- ◆ Large 6 digits LCD (108 mm x 27 mm / 4.25" x 1.06") with backlight
- ◆ Built-in long life rechargeable battery, each charge for approximately 100 hours
- ◆ Rugged aluminum die-casting injection construction
- ◆ Full numerical keyboard for enter of tare weight, sample quantity & average unit weight
- ◆ Auto calibration
- ◆ With RS-232 interface
- ◆ **Optional :**
Stainless steel pole 400 mm or 665 mm



ITEM NO.	MAX-CH30	MAX-C30	MAX-CH60	MAX-C60	MAX-CH120	MAX-C120	MAX-CH300	MAX-C300
CAPACITY	30 kg		60 kg		120 kg		300 kg	
SENSITIVITY	2 g	5 g	5 g	10 g	10 g	20 g	20 g	50 g
PLATFORM SIZE	430x330mm		430x330mm 525x425mm		430x330mm 525x425mm		525x425mm	
POWER SOURCE	6V rechargeable battery							
PACKING	1 set / CTN, N.W.: 10.44 kg, G.W.: 12.30 kg, Cuft: 2.4'							
	1 set / CTN, N.W.: 16.72 kg, G.W.: 18.66 kg, Cuft: 2.9'							

MAX-W Platform Digital Weighing Scale MAX-WH

- ◆ Large single load cell design
- ◆ Indicator with swivel wheels (up, down 45 ° and level 360 °), easy adjust on viewing angle
- ◆ Large 6 digits LCD (168 mm x 51 mm / 6.61" x 2.01")
- ◆ Built- in long life rechargeable battery, each charge for approximately 100 hours
- ◆ Rugged aluminum die-casting injection construction
- ◆ Full tare function
- ◆ Auto calibration
- ◆ Auto zero tracking
- ◆ Check alarm function, fast for re-pack
- ◆ With RS-232 interface
- ◆ **Optional :**
Large LCD back light
Stainless steel pole 400 mm or 665 mm



ITEM NO.	MAX-WH30	MAX-W30	MAX-WH60	MAX-W60	MAX-WH150	MAX-W150	MAX-WH300	MAX-W300
CAPACITY	30 kg		60 kg		150 kg		300 kg	
SENSITIVITY	2 g	5 g	5 g	10 g	10 g	20 g	20 g	50 g
PLATFORM SIZE	430x330mm		430x330mm 525x425mm		430x330mm 525x425mm		525x425mm	
POWER SOURCE	6V rechargeable battery							
PACKING	1 set / CTN, N.W.: 10.44 kg, G.W.: 12.30 kg, Cuft: 2.4'							
	1 set / CTN, N.W.: 16.72 kg, G.W.: 18.66 kg, Cuft: 2.9'							

MAX-WH Series Indicator

- ◆ N≤30000 divisions
- ◆ With RS - 232 interface
- ◆ With weight & quantity warning function
- ◆ Able to built-in 30 records of data
- ◆ **Optional :**
Large LCD back light
- ◆ Packing : 4 sets / CTN
N.W.: 10.56 kg, G.W.: 12.10 kg Cuft:2.1'

